

Hyosung MX7600DAXL

Multi-function Through the Wall ATM

Hyosung branch transformation solutions have been designed to deliver seamless migration of transactions from the teller line to self-service. The **MX7600DAXL** is a multi-function ATM with more features and functionalities than a standard ATM. The **MX7800DAXL** gives consumers the ability to perform more complex transactions. At Hyosung, every ATM product, service, and support system is engineered to be reliable and flexible.

KEY FEATURES

RELIABILITY

- Innovative design and the use of Hyosung manufactured core technologies allows for fast, easy replenishment and reduced downtime
- MX7800DAXL is designed to provide reliability that is second to none in the market, with the highest uptime and with minimum maintenance needs

FLEXIBILITY

- Designed with modular components that allow for easy upgrades of future technology. The ability to upgrade modules provides a financial institution the ability to save on investments in the ATM channel

CAPACITY

- High capacity cash dispense capability and the ability to support large volume transactions

FUNCTIONALITY

- The MX7600DAXL functionality includes bill payment, funds transfer, and mobile top-up in a highly user-friendly interface for maximum convenience

SECURITY

- Hyosung ATMs support both physical and logical defenses against a variety of attacks. Multi-level locked down operating system, white-listing, and encryption combine for a formidable defense



SPECIFICATIONS

DIMENSIONS

- Height: 54.4"
- Width: 28.4"
- Depth: 40.6"
- Weight: 1978 lbs

ENVIRONMENTAL

- Temperature: 32°F – 104°F (0°C~ 40°C)
- Humidity 25% – 85%

SOFTWARE

- Microsoft® Windows® 7,
- Professional/Windows 10 ready

CUSTOMER INTERFACE

- 15" TFT LCD
- Input Method – IR Touch Screen
- Privacy Filter – 15" Filter
- Tilt Screen Monitor
- PIN Pad – PCI 3.0 EPP
- ADA Audio Guidance – Available with earphone jack, speaker
- Card Reader – DIP Reader EMV compliant

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

MEDIA TECHNOLOGY

- Dispense
 - Configurable denominations (4 cassettes)
 - 3,000 notes per cassette
 - Bundle present, bundle retract
- Single Slot Deposit
 - Option for up to 2,000 checks
 - Option for up to 2,000 notes
 - 50 item deposit
 - Reject and retract capability
 - ECB article 6 compliant

SECURITY

- Safes: UL 291 Level 1
- Alarm – Seismic + Heat
- Locking Device – Electronic, mechanical combination lock, Kaba Mas Cencon lock optional
- Security Camera

SERVICING

- Rear access
- State of health indicators across all modules

PRINTER

- Thermal Line Printing – Thermal roll paper
- 3.1" graphical thermal receipt printer

MAIN CONTROLLER

- CPU – I5-4590S 3.7 GHz (H81)
- Expansion Slots – PCI 2EA, PCI Express 1X 1EA, PCI Express 16x 1EA
- Serial Ports – 6 port
- USB Ports – 13 Ports (USB 3.0 : 4, USB 2.0 : 9) + 7 port USB 2.0 Hub
- VGA – GT520 VGA Card (OPL: DVI, SPL : VGA) On-Board VGA
- LAN – 10/100/1000 Mbps On-Board

ADDITIONAL INFORMATION

- Communication – TCP/IP
- Electronic Journal
- System Battery
- NFC – 13.56MHz ISO14443 Type A,B NFC
- Power Supply: AC 110-240V, 50-60 Hz, Back-up battery (reserving last transaction & safe shutdown)